GENERAL REUSE AND EFFLUENT REUSE NOTES

- 1. ALL REUSE AND EFFLUENT REUSE PIPING TO BE OWNED AND MAINTAINED BY THE CITY OF LEESBURG SHALL BE A SOLID PURPLE COLOR.
- 2. REUSE AND EFFLUENT REUSE MAINS SHALL BE PVC CONFORMING TO AWWA C-900, DR 1B FOR PIPE SIZES 4°-12". PIPES 14" & LARGER SHALL BE AWWA C-905, DR 25. PRESSURE CLASS 350 DIP IS AN ACCEPTABLE ALTERNATE. ALL COUPLINGS, CLEANING COMPOUNDS, SOLVENTS, LUBRICANTS, AND PIPE PREPARATION, FOR LAYING, SHALL BE IN ACCORDANCE WITH THE PIPE MANUFACTURERS LATEST RECOMMENDATIONS.
- DEPTH OF REUSE AND EFFLUENT REUSE LINES TO BE 36° MIN. BELOW FINISHED GRADE.
- REUSE AND EFFLUENT REUSE MAINS TO BE LOCATED 5' FROM BACK OF CURB OR EDGE OF PAVEMENT UNLESS OTHERWISE NOTED.
- 5. ALL PIPING CLEARANCES SHALL BE IN ACCORDANCE WITH CHAPTER 62-555.314, F.A.C.
- 6. ALL REUSE AND EFFLUENT REUSE MAINS UNDER PAVEMENT SHALL BE DUCTILE IRON PIPE AND SHALL EXTEND 5' BEYOND THE EDGE OF PAVEMENT OR BACK OF CURB, EXCEPT DIRECTIONAL BORES, WHICH SHALL BE SDR-11 HDPE.
- 7. ALL IRRIGATION SLEEVING UNDER PAVEMENT SHALL EXTEND 5' BEYOND THE EDGE OF PAVEMENT OR BACK OF CURB.
- 8. ALL OTHER REQUIREMENTS OF THE CITY WATER SYSTEM SHALL APPLY TO THE RE-USE SYSTEM.
- PROPER SIGNAGE FOR PUBLIC ACCESS IRRIGATION AREAS TO BE SUPPLIED BY THE DEVELOPER / CONTRACTOR, IN ACCORDANCE WITH CHAPTER B2-610.41B, F.A.C.



City of Leesburg Standard Details



▲ ENGNEERS - ▲ SURVEYORS ▲ PLANNERS

AND ASSOCIATES, INC. 350 North Binolair Avenue () Tovares Florida \$2778 () (352) 343-6481

April 2004

Detail R-1